

Product Selection Guide: Choosing the Right Resurfacing Material for Your Problem Slab

Just like any other concrete repair material, overlays come in many types. They also span the full range of difficulty of application. Follow this guide to get an idea of what system could work for you.

Material	Level of Difficulty	Type	Level of Service	Time to Traffic
SL503 Overlayment	1	Self-leveling cement	Heavy traffic, abrasion resistant	3 hrs foot traffic 16 hrs forklift
SL502 Underlayment	1	Self-leveling cement	Underlayment for tile	4 hrs for tile application
SR Deep Pour HF Epoxy Overlay	2	Screedable epoxy grout topping	Heavy traffic, general chemical exposure	24 hrs for traffic
SR Novolac Epoxy Overlay	2	Screedable Novolac epoxy grout topping	Heavy traffic, Acid exposure	24 hrs for traffic
SR30 Cement Topping	3	Trowelable cement	Heavy traffic, abrasion resistant	24 hrs for traffic
SR15 Cement Topping	3	Trowelable cement	Heavy traffic, abrasion resistant	3 hrs for traffic

Talk to a Concrete Repair expert for more details about your specific application.

WE'RE HERE TO HELP

Have questions you don't see answered here?

Whether you're in need of technical help or are looking for a product or piece of equipment you can't find, we're always happy to point you in the right direction. Give us a call or email us today to talk more about your upcoming project!

Office: (888) 809-2365

Email: info@indconinc.com